

J 80



# A SALES FEATURES

The J80 juice extractor is designed to make large quantities of ultra-fresh juice from any type of fruit and vegetables in just a few seconds. No heating of ingredients. Vitamins are preserved.

## B TECHNICAL FEATURES

J 80 juicer - Single phase. Power: 700 W. Constant speed: 3,000 rpm. Magnetic safety device and motor brake. Stainless-steel bowl and motor unit. Equipped with a large patented automatic feed tube (Ø 79 mm). Stainless-steel juicer basket, grating disc and filter. Extraction rate: 120 l/h, equivalent to one glass of fresh juice every 7 s. Supplied with a large 6.5-litre pulp container, drip tray and special no-splash spout.

## **STANDARDS**

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006, EN 1678 - 1998, EN 60529-2000: IP 55, IP 34.



#### D

Juice extraction rate

120 litres/hour

A glass of ultra-fresh juice in just 7 seconds

## PRODUCT FEATURES

## **MOTOR BASE**

- Induction direct drive motor for intensive use.
- Very powerful, heavy-duty motor so quiet it can be used right in front of the customer
- Power: 700 W
- Stainless-steel bowl and motor unit
- Magnetic safety device and motor brake
- Constant speed: 3,000 rpm

## JUICER FUNCTION

- All-metal juicer boasting our Auto Feed system (Ø 79 mm
  whole apple) for continuous throughput
- Stainless-steel juicer basket, grating disc and filter for easy cleaning and aftercare
- No-splash spout
- High clearance (162 mm), allowing a jug or cocktail glass to be placed underneath the spout
- You can produce up to 135 glasses of juice before having to stop and empty the large-capacity pulp container

C	TE	CHNICAL DATA		
Po	wer	700 Watts		
Electrical datas		Single phase - plug supplied		
Constant speed		3,000 rpm		
Dimensions (LxWxH)		235 x 538 x 506 mm		
Gross weight		13 kg		
	Supply	Amperage	Reference	
	230V/50/1	7 Amp	56000B	
	120V/60/1	9 Amp	56005B	
	220V/60/1	6 Amp	56004B	
	2201/00/1	<b>4</b> / 4		
2	220V/60/1 SAU*	6 Amp	56210B	

<sup>\*</sup>For commercial use only





