

J 100



D

Juice extraction rate

160 litres/hour

A glass of ultra-fresh juice in just 7 seconds

E

PRODUCT FEATURES

MOTOR BASE

- **Induction direct drive motor** for intensive use.
- Very powerful, heavy-duty motor so quiet it can be used right in front of the customer.
- Power: 1,000 W.
- Stainless-steel bowl and motor unit.
- Magnetic safety device and motor brake.
- Constant speed: 3,000 rpm.

JUICER FUNCTION

- All-metal juicer boasting our Auto Feed system (Ø 79 mm = whole apple) for continuous throughput.
- Stainless-steel juicer basket, grating disc and filter for easy cleaning and aftercare.
- No-splash spout.
- Useful height under spout:
 - 247 mm to be used with a blender bowl
 - 205 mm to be used with a jug or glass
- Two ways of using the juicer:
 - continuous pulp ejection with the pulp ejection container. Enables pulp to be continually ejected under the counter top
 - pulp ejected into a container. Large capacity 7.2 litre translucent pulp collector.

A

SALES FEATURES

The J 100 juice extractor is designed to make large quantities of ultra-fresh juice from any type of fruit and vegetables in just a few seconds. Equipped with a continuous pulp ejection container for greater user comfort. Sloping base for optimum evacuation of juice. No heating of ingredients. Vitamins are preserved.

B

TECHNICAL FEATURES

J 100 Ultra juicer - Single phase. Power: 1,000 W. Constant speed: 3,000 rpm. Magnetic safety device and motor brake. Stainless-steel bowl and motor unit. Equipped with a large patented automatic feed tube (Ø 79 mm). Robust centrifugal juicer basket designed for intensive use, stainless steel grating disc and filter. Flow rate: 160 litres/hour or a glass of ultra-fresh juice in 7 seconds. Delivered with a continuous pulp ejection container (strap provided) for continuous ejection of pulp under the counter top, a large 7.2 litre pulp collector; a drip catcher tray and two no-splash spouts: a short spout to be used with a blender bowl and a long spout for jugs and glasses.

STANDARDS

EN 12100-1 and 2 - 2004, EN 60204- 1 - 2006, EN 1678 - 1998, EN 60529-2000: IP 55, IP 34.



C

TECHNICAL DATA

Power	1000 Watts		
Electrical datas	Single phase - plug supplied		
Constant speed	3,000 rpm		
Dimensions (LxWxH)	262 x 566 x 628 mm		
Gross weight	15,6 kg		
	Supply	Amperage	Reference
	230V/50/1	8 Amp	56100B
	120V/60/1	9 Amp	56105B
	220V/60/1	8 Amp	56104B
	220V/60/1 SAU*	8 Amp	56110B

*For commercial use only

