



GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
<b>6+6 x GN</b> <b>1/1</b> <b>80mm spacing</b>	<b>W: 525mm</b> <b>D: 750mm</b> <b>H: 1695mm</b>	<b>W: 330mm</b> <b>D: 540mm</b> <b>H: 508mm</b>	<b>W: 330mm</b> <b>D: 540mm</b> <b>H: 508mm</b>	<b>134 kg</b>	<p><b>Exterior walls:</b> ABS plastic.  <b>Inner container:</b> Welded container in stainless steel.  <b>Guides:</b> Stainless steel, pressed from the inner container.  <b>Insulation:</b> Polyurethane foam.  <b>Door:</b> Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.  <b>Wheels:</b> Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.  <b>Top frame:</b> Stainless steel and PVC corners.  <b>Trolley frame:</b> Rejected list of galvanized steel coated with PVC.  <b>K:</b> Efficient convection cooling with electronic temperature control 230V/245W, insulation class IP44.  <b>F:</b> Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/550W. CE and S mark.</p>
<p>230V/245W AC + 230V/550W  <b>Product number:</b> 122215-ZKF  SDX Thermobox KF180 (6+6 GN 1/1) Single handed grip handle</p> <p>230V/245W AC + 230V/550W  <b>Product number:</b> 122215-XKF  SDX Thermobox KF180 (6+6 GN 1/1) Eccentric lock</p>					