




SPACE 40 EASY



- "Easy" identifies a simplified control board that provides all the main functions necessary for a complete professional use.
- All the other technical and functional specifications of the machine are the same as in the amplified version.
- Easy vacuum and sealing time setting.
- Display of vacuum percentage and time to countdown.
- Last setting saved in memory.
- Rev counter and pump meter.
- Pump preheating and oil cleaning cycle.
- Oil change message.
- Timed external vacuum.
- **Not available with printer or Gas.**
- Large injection bells.
- Automatic cover lift operated by pneumatic pistons.
- Easily removable sealing bar.



Model	40 Easy DS 12	40 Easy DX 12	40 Easy DS	40 Easy DX	40 Easy BX
Power	kw 0,75	kw 0,75	kw 0,75	kw 0,75	kw 0,75
Power source	230V 50Hz F+N	230V 50Hz F+N	230V 50Hz F+N	230V 50Hz F+N	230V 50Hz F+N
Cavity dimensions	mm 430x410x160h.	mm 430x410x160h.	mm 430x410x160h.	mm 430x410x160h.	mm 430x410x160h.
Vacuum pump	12 mc/h	12 mc/h	21 mc/h	21 mc/h	21 mc/h
Sealing bar	mm 410	mm 410	mm 410	mm 410	mm 410
A	mm 493	mm 493	mm 493	mm 493	mm 493
B	mm 585	mm 585	mm 585	mm 585	mm 585
C	mm 370	mm 370	mm 370	mm 370	mm 370
D	mm 542	mm 542	mm 542	mm 542	mm 542
E	mm 390	mm 390	mm 390	mm 390	mm 390
F	mm 430	mm 430	mm 430	mm 430	mm 430
G	mm 85	mm 85	mm 85	mm 85	mm 85
H	mm 170	mm 170	mm 170	mm 170	mm 170
Net weight	56 Kg	56 Kg	56 Kg	56 Kg	56 Kg
Shipping dimensions	760x640x770 mm	760x640x770 mm	760x640x770 mm	760x640x770 mm	760x640x770 mm
Gross weight	66 Kg	66 Kg	66 Kg	66 Kg	66 Kg