

Modello - Model - Model - Gerätetyp - Modelo			AB05E5040	AB5TE5040	AB10E4040	AB11E4040	AB14E4040	AB21E4040
								
	Descrizione - Description Description - Beschreibung - Descripción		5T 1/1	5T 1/1	10T 1/1	10TR 1/1	14T 1/1	10T 2/1
	Tipo di teglie - Trays type - Type de plateaux Blechtyp - Tipo de fuentes		GN 1/1 600x400	GN 1/1 600x400	GN 1/1 600x400	GN 1/1 600x400	GN 1/1 600x400	GN 2/1 600x800
	Capacità Massima - Teglie H=65 - Max load capacity Trays H=65 - Capacité maximale - Plateaux H=65 Fassungsvermögen - Bleche H=65 Número máximo de fuentes H=65	N°	5	5	10	10	14	6 (H=65mm) 10 (H=40mm)
	Interasse griglie - Grids pitch - Pas des grilles Gitterabsatz - Intereje fuentes	mm	70	70	75	75	67	50/75
	Ciclo Positivo - Positive cycle - Cycle positif Positiver Zyklus	kg	20	20	40	40	55	75
	Ciclo Negativo - Negative cycle - Cycle negatif Negativer Zyklus	kg	12	12	25	25	35	50
	Dimensioni esterne - External Dimension Dimensions externes - ußenabmessungen Dimensiones externas							
	Lunghezza - Width -Largeur - Breite - Anchura	mm	784	784	800	800	800	1050
	Profondità / con porte aperte Depth / with open doors Profondeur avec portes ouverte Tiefe/mit geöffneter Tü Profundidad / con puerta abierta	mm	800/1545	800/1545	825/1585	900/1660	825/1585	1080/1840
	Altezza - Height - Hauteur - Höhe - Altura	mm	900	900	1800	1800	2025	1900
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen - Dimensiones internas							
	Lunghezza - Width -Largeur - Breite - Anchura	mm	664	664	664	435	664	664 / 910
	Profondità - Depth - Profondeur - Tiefe - Profundidad	mm	410	410	415	664	415	905
	Altezza - Height - Hauteur - Höhe	mm	370	370	870	870	1095	870
	Compressor							
	Model		NT2180GK	NT2180GK	H181CS	H181CS	H201CS	H290CS
	Potenza - Power - Puissance - Leistung	HP	1	1	1,8	1,8	2	2,9
	T° Evaporation	°C	-10	-10	-10	-10	-10	-10
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	1700	1700	4500	4500	5800	7200
	Potenza Riscaldamento - Heating Power Puissance de chauffage - Heizleistung Potencia de calefacción	W	500	500	1000	1000	1500	1600
	Potenza assorbita - Total Power - Puissance Leistung - Potencia	W - A	1050 - 5	1050 - 5	2500	2500	3000	2500
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung - Alimentación	V	230V~ 50Hz	230V~ 50Hz	400V 3N~ 50Hz	400V 3N~ 50Hz	400V 3N~ 50Hz	400V 3N~ 50Hz