


KWC GASTRO E

Lever mixer - Commercial kitchen

Modell-Linie: GASTRO E | 24.561.144.700FL

Taps | Dishwashing





KWC-No.

stainless steel, A 200, B 270, flexible connection hoses

- * Lever mixer
 * Suspension spring
 * TouchProtect anti-scald protection thanks to the "double skin" * TouchProtect - anti-scald protection thanks to the "double skin" principle
 * Intrinsically safe against backflow and cross flow
 * Swivel spout
 - with adjustable gland
 - Jet regulator
 * Pre-rinse spray
 - with integrated delayed closing device to minimize water hammer
 - with valve maintenance unit for cleaning and swivelling sieve jet
 - SprayClean - easy to clean and actively prevents limescale

buildup

- Surface SprayLock lockable jet spray
 PowerClean needle spray mode
 * OptimalSpace ample space for washing or working
 * KWC cartridge XL 46 high capacity
 with ceramic discs

- with ceramic aiscs
 flow rate and temperature continuously variable
 temperature limitation
 * Flexible connection hoses ½" with transition to ¾"
 * Fastening by means of threaded sleeve 1 ¼"
 * Mounting hole size ø42 mm



Technical Data

| Flow rate | |
|------------------------------|----------|
| Spray: Flow rate | |
| Connection | |
| Spout | |
| Handling | |
| Kitchen_spray | |
| Projection B | |
| Color code | |
| Installation_type | |
| Faucet_typ | |
| Dimension Height | |
| Acoustic group | |
| Spray outlet: Acoustic group | |
| Projection_A | <u>-</u> |
| Dimension Water outlet | |
| material | _ |

| 27 l/min (3 bar) |
|---------------------------|
| 15 l/min (3 bar) |
| Flexible connection hoses |
| swivel |
| side lever |
| Pre-rinse spray |
| B 270 |
| stainless steel |
| Pillar installation |
| Faucet |
| 1020 |
| Mains receiver1 |
| Battery1 |
| A 200 |
| 275/194 |
| stainless steel |
| |
| |











