

VOLANO B116SA











	A	В	C	D	E		C	H	100	-
	mm	mm								
B116SA	260	290	260	590	550	755	960	780	720	55

	K.
Speditiche elettriche	Dimensione im ballo
Electrical specifications	Packaging dimensions
Caractéristiques électriques	Dim. emballage
Elektrische Eigenschaften	Verpack. abmess ungen

0				
- Ned IIST	Stand	Socie	Sockel	

		Ø Lama Ø Blade Ø Lame Ø Mess er		Spessore taglio Cut thickness Epaisser de coupe Schnittbreite	Peso netto Net weight Poids net Nettogewicht	Potenza motore Motor rating Puissance moteur Motorleistung	Specifiche elettriche Electrical specificatio Caractéristiques élect Elektrische Eigenscha	Dimensione imballo Packaging dimension Dim. emballage Verpack. abmessung	Piedistallo Stand Socke Sockel	Imballo piedistallo Stand packaging Emballage Sode Sockel Verpack.
mm mm kg kW V - Hz cm - kg cm - kg		mm		mm	kg	kW	V - Hz	cm - kg	cm - kg	cm - kg
B116SA 370 0 - 4 110 0.75 230/50/1 110x110x118h - 150 57x62x87h - 53 74x80x95h - 76	B116SA	370	B116SA	0 - 4	110	0,75		110x110x118h - 150	57x62x87h - 53	74x80x95h - 76

Farve sort ekskl. Understel Professional semi-automatic electric slicer

- Flower flywheel
- Aluminium structure
- Centesimal slice thickness adjustment system with incremental precision
- Stainless steel slice deflector, receiving tray, sliding overplate
- 360° blade guard ring with mechanised activation
- Automatic coordinated advance system with thickness gauge plate to ensure immediate straight cutting with no waste
- Stainless steel sliding overplate, easily removed for cleaning
- Built-in sharpener with coordinated spring activation