

# Specification/Data sheet

## Exhaust hood Combi-Duo models 6-1/1, 10-1/1



Article number: 60.76.221

### Description

The exhaust hood extracts steam from the cooking cabinet via the external connection (without condensation technology). Installation is simple, and the hood can be retrofitted at any time.

### Features

- Intelligent power control with automatic, continuously variable adjustment of the extraction power to the quantity of steam emitted
- Automatically boosts extraction rate when cooking cabinet door is opened
- Connects to both iCombi cooking systems in a Combi-Duo
- Eliminates lingering steam and vapours as they are discharged to the outside
- Reduces expenses and costs for ventilation
- Easy to install and retrofit
- Issue of service notifications on the display of the iCombi Pro and iCombi Classic
- Adjustment of maximum extraction power on the display
- Easy to clean baffle plate, dishwasher safe

### Technical Specifications

- Connection: 230V - 1 NAC 50/60 Hz
- Connected load: 170 W
- Extraction capacity: 705 m<sup>3</sup>/h
- Operating noise level: min 50 dBA; max 65 dBA
- Width: 854 mm
- Height: 359 mm
- Depth: 970 mm
- Weight: 50 kg
- Connection diameter for the external connection: 200mm

### Material

- Rust-free stainless steel (CNS 1.4301)

### Note

- A connection to the outside is needed to extract the vapours
- To install an UltraVent, UltraVent Plus or exhaust hood on a SelfCookingCenter (from 09/2011) or CombiMaster Plus, a corresponding adapter kit is required
- The local standards and regulations for ventilation systems must be adhered to
- Only permitted for installation on electrical units

Specification/Data sheet

Exhaust hood Combi-Duo models 6-1/1, 10-1/1

