

## PREMIER M 60 C DR

Produktserie: Premier

Varenummer: 172602010



The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 5), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stable stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into low-ceiling environments, yet convince with a surprisingly high internal volume. The Premier M 60 C DR is a with a net internal volume of 335. The dimensions are 610 x 920 x 2075 mm.

### "FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. Additionally, the automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal and reduce escaping of cold air.

**COMPARTMENTALIZED DESIGN** The PREMIER's condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it can easily be serviced via the front flap on top of the cabinet.

### LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier M 60 C DR runs on natural refrigerant and has [5].

### ERGONOMIC & EASY TO USE

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real-time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

### HYGIENE & WASTE REDUCTION

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

### EASY CUSTOMIZATION & FLEXIBILITY PREMIER

cabinets can easily be adjusted to your requirements, for example, the length of the legs, the position of the door, and the foot pedal. They also can accommodate shelves up to 18-22 levels (4 shelves included) offering you high flexibility to accommodate different types of produce. "

## SPECIFIKATION

Temperaturområde	-5/+12°C	Energiforbrug Ecodesign AEC (kWh/år)	286
Rumindhold, brutto (liter)	480	Energieffektivitetsklasse (ISO 22041-2019)	A
Netto nyttevolum (liter)	335	Energieffektivitetsindeks	24.71
Udvendig	Rustfrit stål AISI 304	Lydniveau – dB(A)	46
Indvendig	Rustfri stål AISI 304	Klimaklasse	5
Mål B x D x H (mm)	610 x 920 x 2075	Ben / hjul	H = 125 mm (C2)
Vægt, brutto (kg)	120	Kølemiddel (kg)	0.08
Isolering (mm)	80 mm (polyurethane)	CO2 ækvivalent (kg)	0.24
Kølemiddel	R600a	GN – hyldestørrelse	Hylde Euronorm 40x60 cm   Velegnet til 1/1 EN-system
GWP	3	Maksimal antal hylder	25
Kølekapacitet ved -10°C (Watt)	206	Antal hylder	4
Eltilslutning	230V, 50 Hz	Udstyret med	Right hand hinged reversible door with lock, automatic door closing, pedal door opener, 4 grey shelves, LED lighting
Tilslutningseffekt (Watt)	120	Dørtype	Isoleret dør