




**ENERG**  
енергия · ενεργεια



**HOSHIZAKI**

**PREMIER K 2 A**  
**3D 3D**

**A+++**

**A++**

**A+**

**A**

**B**

**C**

**D**

**E**

**F**

**G**

**A**

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ  
ENERGIJA · ENERGY · ENERGIE  
ENERGI

**390**  
kWh/annum



**155 L**



**- L**



**5**  
40°C-40%

2015/1094-IV

# PRODUCT FICHE

Supplier / trade mark

**HOSHIZAKI**

Model name:

**PREMIER K 2 A 3D 3D**

Type of model:

Chilled operating temperature

**X**

Frozen operating temperature

Multi use cabinet

Vertical cabinet

Counter cabinet

**X**

Parameter	Symbol	Value	Unit
Energy Efficiency Class	EEC	<b>A</b>	
Energy Efficiency Index	EEI	<b>17,85</b>	
24 hour Energy Consumption	E24h	<b>1,069</b>	kWh
Annual Energy Consumption	AEC	<b>390,18</b>	kWh
Net volume for compartment 1	V <sub>N</sub>	<b>77,4</b>	liters
Net volume for compartment 2	V <sub>N</sub>	<b>77,4</b>	liters
Net volume for compartment 3	V <sub>N</sub>	-	liters
Net volume for compartment 4	V <sub>N</sub>	-	liters
Refrigerant R600a	-	<b>0,07</b>	kg
CO2 Equivalent	-		tonnes
Climate class	CC	<b>5</b> 40°C, 40 rH%	

This appliance is intended for use in ambient temperature up to 40°C