

Product data sheet Industrial basket 44 lt.



Product(description)	Product code	Material
Industrial basket 44 lt. blue	0700045	LLDPE
Industrial basket 44 lt. orange	0700046	LLDPE

Capacity	Litres	Gallons
Industrial basket 44 lt. blue	44	11,5
Industrial basket 44 lt. orange	44	11,5

Weight	Grams	Ounces
Industrial basket 44 lt. blue	1700	59,96
Industrial basket 44 lt. orange	1700	59,96

Product identification	
Manufacturer ID	: bottom basket
Date Clock	: bottom basket
Country of origin	: The Netherlands

Temperature
Recommended temperature for normal use is a maximum of 70°C/158°F
The peak melting temperature is 123°C/253°F (the point the material melts)
The Vicat softening temperature is 96°C/205°F (the point the material is at a temperature that there is a pin to pass through with minimal pressure)
With this information we would not recommend to use the industry basket under conditions of 80/90° - 176/194°F or higher, since the live span of the basket is then minimal
Use and circumstances surrounding the 50/60°C- 122/140°F are no problem

Other information
DoC available on request
ISO Certificate manufacturer available on request
Product Data Sheet material LLDPE available on request
Other colors available on request

Dimensional tolerances	%
Height and diameter	± 2.5

Weight tolerance
All baskets have a tolerance of ± 4 % on the initial weight mentioned on this data sheet